

공개 S/W 기술지원

NHN

한국소프트웨어진흥원
공개SW기술지원센터

<Revision 정보>

일자	VERSION	변경내역	작성자
2007. 5. 3	0.1	초기 작성	손명선

공개SW 기술지원	
	구분 : 기술지원
	단계:
	작성자: 순명선
	작성일: 2007.5.3
	검토자:
	검토일:
	승인자:
	승인일:

1. 대상기업/기관 정보

구분	항목	내용	비고
기업/기관 정보	지역	경기도 성남시 분당구 정자동 206번지 KT IDC	
	기업/기관 명칭	(주)NHN	
	부서	서비스기술팀	
	직책	과장	
	담당자 이름	김욱(시디네트웍스)	
	전화번호 / 팩스번호	010-6737-6263 / 02-569-5832	
	E-Mail	ceci13@cdnetworks.co.kr	

2. 대상기업/기관 지원사항

구분	항목	내용	비고
기업/기관 지원사항	접수내용	NHN 네이버 UCC 컨텐츠 제어 분배 서버 이중화 구축 (MySQL DB서버 Active/Standby HA 클러스터 구축)	
	지원내역	<p>1. 설치 환경 파악</p> <pre>[root@krkt06uldh06 src]# uname -a Linux krkt06uldh06 2.6.9-42.ELsmp #1 SMP Tue Aug 15 10:35:26 BST 2006 x86_64 x86_64 x86_64 GNU/Linux [root@krkt06uldh06 src]# ifconfig eth0 Link encap:Ethernet HWaddr 00:A0:D1:E6:00:32 inet addr:61.78.57.177 Bcast:61.78.57.191 Mask:255.255.255.224 inet6 addr: fe80::2a0:d1ff:fee6:32/64 Scope:Link UP BROADCAST RUNNING MULTICAST MTU:1500 Metric:1 RX packets:175682 errors:0 dropped:0 overruns:0 frame:0 TX packets:16382 errors:0 dropped:0 overruns:0 carrier:0 collisions:0 txqueuelen:1000 RX bytes:36911507 (35.2 MiB) TX bytes:2502626 (2.3</pre>	

	<pre>MiB) Interrupt:201 eth1 Link encap:Ethernet HWaddr 00:A0:D1:E6:00:33 inet addr:192.168.100.200 Bcast:192.168.100.255 Mask:255.255.255.0 inet6 addr: fe80::2a0:d1ff:fee6:33/64 Scope:Link UP BROADCAST RUNNING MULTICAST MTU:1500 Metric:1 RX packets:148 errors:0 dropped:0 overruns:0 frame:0 TX packets:99 errors:0 dropped:0 overruns:0 carrier:0 collisions:0 txqueuelen:1000 RX bytes:16395 (16.0 KiB) TX bytes:11195 (10.9 KiB) Interrupt:209 lo Link encap:Local Loopback inet addr:127.0.0.1 Mask:255.0.0.0 inet6 addr: ::1/128 Scope:Host UP LOOPBACK RUNNING MTU:16436 Metric:1 RX packets:8 errors:0 dropped:0 overruns:0 frame:0 TX packets:8 errors:0 dropped:0 overruns:0 carrier:0 collisions:0 txqueuelen:0 RX bytes:560 (560.0 b) TX bytes:560 (560.0 b)</pre>
	<p>2. Encluster HA 패키지 압축 해제</p> <pre>[root@krkt06uldh06 clunix]# tar zxvf EnClusterHA_x86_64.tar.gz ./EnCluster/ ./EnCluster/setup ./EnCluster/source/ ./EnCluster/source/heartbeat-2.0.2-1.i386.rpm ./EnCluster/source/DBI-1.53.tar.gz ./EnCluster/source/cmdb-1.6.5-cez.i386.rpm ./EnCluster/source/heartbeat-ldirectord-2.0.2-1.x86_64.rp m ./EnCluster/source/heartbeat-stonith-2.0.2-1.x86_64.rpm ./EnCluster/source/mkdrbddev</pre>

	<pre>./EnCluster/source/heartbeat-2.0.7-clx.i386.rpm ./EnCluster/source/libnet-1.1.2.1-clx.x86_64.rpm ./EnCluster/source/libnet-debuginfo-1.1.2.1-clx.x86_64.rpm ./EnCluster/source/heartbeat-stonith-2.0.2-1.i386.rpm ./EnCluster/source/heartbeat-pils-2.0.2-1.i386.rpm ./EnCluster/source/DBD-mysql-3.0008/ ./EnCluster/source/DBD-mysql-3.0008/Makefile.PL ./EnCluster/source/DBD-mysql-3.0008/eg/ ./EnCluster/source/DBD-mysql-3.0008/eg/proc_example1.pl ./EnCluster/source/DBD-mysql-3.0008/eg/prepare_memory_usage.pl ./EnCluster/source/DBD-mysql-3.0008/eg/proc_example2.pl ./EnCluster/source/DBD-mysql-3.0008/eg/proc_example3.pl ./EnCluster/source/DBD-mysql-3.0008/dbdimp.o ./EnCluster/source/DBD-mysql-3.0008/ChangeLog ./EnCluster/source/DBD-mysql-3.0008/mysql.c ./EnCluster/source/DBD-mysql-3.0008/INSTALL.html ./EnCluster/source/DBD-mysql-3.0008/mysql.bs ./EnCluster/source/DBD-mysql-3.0008/dbdimp.h ./EnCluster/source/DBD-mysql-3.0008/Makefile ./EnCluster/source/DBD-mysql-3.0008/mysql_xs ./EnCluster/source/DBD-mysql-3.0008/mysql_xsi ./EnCluster/source/DBD-mysql-3.0008/lib/ ./EnCluster/source/DBD-mysql-3.0008/lib/Mysql.pm ./EnCluster/source/DBD-mysql-3.0008/lib/Mysql/ ./EnCluster/source/DBD-mysql-3.0008/lib/Mysql/Statement.pm ./EnCluster/source/DBD-mysql-3.0008/lib/Bundle/ ./EnCluster/source/DBD-mysql-3.0008/lib/Bundle/DBD/ ./EnCluster/source/DBD-mysql-3.0008/lib/Bundle/DBD/mysql.pm ./EnCluster/source/DBD-mysql-3.0008/lib/DBD/ ./EnCluster/source/DBD-mysql-3.0008/lib/DBD/mysql/ ./EnCluster/source/DBD-mysql-3.0008/lib/DBD/mysql/GetI</pre>
--	--

	<pre>nfo.pm ./EnCluster/source/DBD-mysql-3.0008/lib/DBD/mysql/INST ALL.pod ./EnCluster/source/DBD-mysql-3.0008/lib/DBD/mysql.pm ./EnCluster/source/DBD-mysql-3.0008/mysql.o ./EnCluster/source/DBD-mysql-3.0008/pm_to_blib ./EnCluster/source/DBD-mysql-3.0008/constants.h ./EnCluster/source/DBD-mysql-3.0008/t/ ./EnCluster/source/DBD-mysql-3.0008/t/40bindparam.t ./EnCluster/source/DBD-mysql-3.0008/t/60leaks.t ./EnCluster/source/DBD-mysql-3.0008/t/prepare_noerror.t ./EnCluster/source/DBD-mysql-3.0008/t/40blobs.t ./EnCluster/source/DBD-mysql-3.0008/t/param_values.t ./EnCluster/source/DBD-mysql-3.0008/t/42bindparam.t ./EnCluster/source/DBD-mysql-3.0008/t/10dsnlist.t ./EnCluster/source/DBD-mysql-3.0008/t/40bindparam2.t ./EnCluster/source/DBD-mysql-3.0008/t/35prepare.t ./EnCluster/source/DBD-mysql-3.0008/t/41blobs_prepare.t ./EnCluster/source/DBD-mysql-3.0008/t/50chopblanks.t ./EnCluster/source/DBD-mysql-3.0008/t/lib.pl ./EnCluster/source/DBD-mysql-3.0008/t/41bindparam.t ./EnCluster/source/DBD-mysql-3.0008/t/_prepare_noerror. t ./EnCluster/source/DBD-mysql-3.0008/t/50commit.t ./EnCluster/source/DBD-mysql-3.0008/t/35limit.t ./EnCluster/source/DBD-mysql-3.0008/t/40nulls.t ./EnCluster/source/DBD-mysql-3.0008/t/20createdrop.t ./EnCluster/source/DBD-mysql-3.0008/t/dbdadmin.t ./EnCluster/source/DBD-mysql-3.0008/t/30insertfetch.t ./EnCluster/source/DBD-mysql-3.0008/t/mysql.mtest ./EnCluster/source/DBD-mysql-3.0008/t/40numrows.t ./EnCluster/source/DBD-mysql-3.0008/t/texecute.t ./EnCluster/source/DBD-mysql-3.0008/t/insertid.t ./EnCluster/source/DBD-mysql-3.0008/t/40listfields.t ./EnCluster/source/DBD-mysql-3.0008/t/00base.t ./EnCluster/source/DBD-mysql-3.0008/t/mysql.dbtest ./EnCluster/source/DBD-mysql-3.0008/Makefile.PL.embedd ed</pre>
--	---

	<pre>./EnCluster/source/DBD-mysql-3.0008/TODO ./EnCluster/source/DBD-mysql-3.0008/MANIFEST.SKIP ./EnCluster/source/DBD-mysql-3.0008/myld ./EnCluster/source/DBD-mysql-3.0008/META.yml ./EnCluster/source/DBD-mysql-3.0008/dbdimp.c ./EnCluster/source/DBD-mysql-3.0008/blib/ ./EnCluster/source/DBD-mysql-3.0008/blib/arch/ ./EnCluster/source/DBD-mysql-3.0008/blib/arch/auto/ ./EnCluster/source/DBD-mysql-3.0008/blib/arch/auto/DBD / ./EnCluster/source/DBD-mysql-3.0008/blib/arch/auto/DBD /mysql/ ./EnCluster/source/DBD-mysql-3.0008/blib/arch/auto/DBD /mysql/.exists ./EnCluster/source/DBD-mysql-3.0008/blib/arch/auto/DBD /mysql/mysql.bs ./EnCluster/source/DBD-mysql-3.0008/blib/arch/auto/DBD /mysql/mysql.so ./EnCluster/source/DBD-mysql-3.0008/blib/lib/ ./EnCluster/source/DBD-mysql-3.0008/blib/lib/Mysql.pm ./EnCluster/source/DBD-mysql-3.0008/blib/lib/Mysql/ ./EnCluster/source/DBD-mysql-3.0008/blib/lib/Mysql/State ment.pm ./EnCluster/source/DBD-mysql-3.0008/blib/lib/auto/ ./EnCluster/source/DBD-mysql-3.0008/blib/lib/auto/DBD/ ./EnCluster/source/DBD-mysql-3.0008/blib/lib/auto/DBD/m ysql/ ./EnCluster/source/DBD-mysql-3.0008/blib/lib/auto/DBD/m ysql/.exists ./EnCluster/source/DBD-mysql-3.0008/blib/lib/Bundle/ ./EnCluster/source/DBD-mysql-3.0008/blib/lib/Bundle/DBD / ./EnCluster/source/DBD-mysql-3.0008/blib/lib/Bundle/DBD /mysql.pm ./EnCluster/source/DBD-mysql-3.0008/blib/lib/DBD/ ./EnCluster/source/DBD-mysql-3.0008/blib/lib/DBD/mysql/ ./EnCluster/source/DBD-mysql-3.0008/blib/lib/DBD/mysql/ GetInfo.pm</pre>
--	---

	<pre>./EnCluster/source/DBD-mysql-3.0008/blib/lib/DBD/mysql/INSTALL.pod ./EnCluster/source/DBD-mysql-3.0008/blib/lib/DBD/.exists ./EnCluster/source/DBD-mysql-3.0008/blib/lib/DBD/mysql.pm ./EnCluster/source/DBD-mysql-3.0008/blib/man3/ ./EnCluster/source/DBD-mysql-3.0008/blib/man3/.exists ./EnCluster/source/DBD-mysql-3.0008/blib/man3/DBD::mysql::INSTALL.3pm ./EnCluster/source/DBD-mysql-3.0008/blib/man3/DBD::mysql.3pm ./EnCluster/source/DBD-mysql-3.0008/blib/man3/Mysql.3pm ./EnCluster/source/DBD-mysql-3.0008/blib/man3/Bundle::DBD::mysql.3pm ./EnCluster/source/DBD-mysql-3.0008/MANIFEST ./EnCluster/source/DBD-mysql-3.0008/README ./EnCluster/source/cluman-1.6.5h-cez.i386.rpm ./EnCluster/source/libnet-1.1.2.1-clx.src.rpm ./EnCluster/source/heartbeat-debuginfo-2.0.2-1.x86_64.rpm ./EnCluster/source/heartbeat-2.0.2-1.x86_64.rpm ./EnCluster/source/heartbeat-2.0.2-1.src.rpm ./EnCluster/source/DBD-mysql-3.0008.tar.gz ./EnCluster/source/heartbeat-pils-2.0.7-clx.i386.rpm ./EnCluster/source/heartbeat-pils-2.0.2-1.x86_64.rpm ./EnCluster/source/drbd-0.7.16.tar.gz ./EnCluster/source/libnet-1.1.2.1-clx.i386.rpm ./EnCluster/source/heartbeat-stonith-2.0.7-clx.i386.rpm ./EnCluster/module/ ./EnCluster/module/mysql_mon ./EnCluster/module/connective_mon ./EnCluster/module/MysqlCheck ./EnCluster/module/authkeys ./EnCluster/module/NetCheck ./EnCluster/module/mysql.monitor ./EnCluster/config/ ./EnCluster/config/snapshot.cdb</pre>
--	--

```
./EnCluster/config/erbd.cf
./EnCluster/config/ha.cf
./EnCluster/config/hacommand.cf
./EnCluster/config/nodeinfo.cf
```

3. Installer를 이용한 설치

```
[root@krkt06uldh06 EnCluster]# ./setup ccd
/usr/local/mysql/
[root@krkt06uldh06 EnCluster]# ./setup
```

```
===== EnCluster HA Installer =====
```

```
### SELECT ONE ON MENU ###
```

1. Install PERL Module
2. Install EnCluster Admin
3. Install EnCluster HA
4. Install ERBD (Replication)
5. Configuration
6. EXIT

```
#####
```

```
:2
```

```
===== EnCluster HA Installer =====
```

```
### SELECT ONE ON MENU ###
```

1. Install CMDB Cluman
2. Config CIP
3. Input the License KEY
4. Patch
5. go to MAIN MENU

```
#####
```

```
:1
```

```
Install CMDB Cluman
```

```
===== EnCluster HA Installer =====
```

```
### SELECT ONE ON MENU ###
```

1. Install CMDB Cluman
2. Config CIP
3. Input the License KEY
4. Patch
5. go to MAIN MENU

```
#####
```

```
:2
```

```
Config CIP
```

```
Please input the Cluster IP Address! ex)
```

```
192.168.123.100 : 61.78.57.170
```

```
Your Cluster IP is 61.78.57.170
```

```
Do you want to continue.. Please press any keys !!
```

```
===== EnCluster HA Installer =====
```

```
### SELECT ONE ON MENU ###
```

1. Install CMDB Cluman
2. Config CIP
3. Input the License KEY
4. Patch
5. go to MAIN MENU

```
#####
```

```
:3
```

```
Config the License KEY
```

```
Please input the EnCluster HA License! ex)
```

```
ENC16-XXXXXX-XXXXXX-XXXXXX-XXXXXX-XXXXXX
```

```
===== EnCluster HA Installer =====
```

```
### SELECT ONE ON MENU ###
```

1. Install CMDB Cluman
2. Config CIP
3. Input the License KEY
4. Patch
5. go to MAIN MENU

```
#####
```

:4

Patch

Patch is completed !!Do you want to continue.. Please
press any keys !!

==== EnCluster HA Installer ====

```
### SELECT ONE ON MENU ###
```

1. Install CMDB Cluman
2. Config CIP
3. Input the License KEY
4. Patch
5. go to MAIN MENU

```
#####
```

:5

==== EnCluster HA Installer ====

```
### SELECT ONE ON MENU ###
```

1. Install PERL Module
2. Install EnCluster Admin
3. Install EnCluster HA
4. Install ERBD (Replication)
5. Configuration
6. EXIT

```
#####
```

	<pre>:3 ===== EnCluster HA Installer ===== ### SELECT ONE ON MENU ### 1. Install PERL Module 2. Install EnCluster Admin 3. Install EnCluster HA 4. Install ERBD (Replication) 5. Configuration 6. EXIT ##### :4 ===== EnCluster HA Installer ===== ### SELECT ONE ON MENU ### 1. Install ERBD Replication 2. go to MAIN MENU ##### :1 Install ERBD Replication ===== EnCluster HA Installer ===== ### SELECT ONE ON MENU ### 1. Install PERL Module 2. Install EnCluster Admin 3. Install EnCluster HA 4. Install ERBD (Replication) 5. Configuration</pre>	
--	--	--

```
6. EXIT

#####
:5

===== EnCluster HA Installer =====

### SELECT ONE ON MENU ###

1. Configure
2. go to MAIN MENU

#####
:1
Configuration
Do you want to continue.. Please press any keys !!

===== EnCluster HA Installer =====

### SELECT ONE ON MENU ###

1. Configure
2. go to MAIN MENU

#####
:2

===== EnCluster HA Installer =====

### SELECT ONE ON MENU ###

1. Install PERL Module
2. Install EnCluster Admin
3. Install EnCluster HA
4. Install ERBD (Replication)
5. Configuration
6. EXIT
```

```
#####  
:  
:
```

4. ERBD 패키지 업그레이드 설치

```
[root@krkt06uldh06 drbd-0.7.23]# cd drbd  
[root@krkt06uldh06 drbd]# ls  
drbd_actlog.c           drbd_proc.c  
lru_cache.c  
drbd_bitmap.c          drbd_receiver.c  
lru_cache.h  
drbd_buildtag.c         drbd_req.c  
Makefile  
drbd_compat_types.h     drbd_sizeof_sanity_check.c  
Makefile-2.4  
drbd_compat_wrappers.h  drbd_worker.c  
Makefile-2.6  
drbd_fs.c                hlist.h  
mempool-2.4.c  
drbd_int.h              Kconfig  
mempool.h  
drbd_main.c             linux  
[root@krkt06uldh06 drbd]# make clean  
rm -rf .tmp_versions  
rm -f *.oas *.ko *.cmd *.d *.tmp *.mod.c *.flags  
.depend .kernel*  
[root@krkt06uldh06 drbd]# ls  
drbd_actlog.c           drbd_proc.c  
lru_cache.c  
drbd_bitmap.c          drbd_receiver.c  
lru_cache.h  
drbd_buildtag.c         drbd_req.c  
Makefile  
drbd_compat_types.h     drbd_sizeof_sanity_check.c  
Makefile-2.4  
drbd_compat_wrappers.h  drbd_worker.c  
Makefile-2.6  
drbd_fs.c                hlist.h
```

```
mempool-2.4.c
drbd_int.h          Kconfig
mempool.h
drbd_main.c         linux
[root@krkt06uldh06 drbd]# cd ..
[root@krkt06uldh06 drbd-0.7.23]# ls
benchmark  documentation  drbd.spec.in  README
upgrade_0.6.x_to_0.7.0.txt
ChangeLog  drbd        INSTALL      scripts
upgrade_0.7.0_to_0.7.1.txt
COPYING    drbd_config.h  Makefile     testing  user
[root@krkt06uldh06 drbd-0.7.23]# make tools
make -C drbd drbd_buildtag.c
make[1]: Entering directory
`/usr/local/src/clunix/drbd-0.7.23/drbd'
make[1]: Leaving directory
`/usr/local/src/clunix/drbd-0.7.23/drbd'
make[1]: Entering directory
`/usr/local/src/clunix/drbd-0.7.23/user'
gcc -c -Wall -I..../drbd -c -o drbdsetup.o drbdsetup.c
gcc -c -Wall -I..../drbd -c -o ..../drbd/drbd_buildtag.o
..../drbd/drbd_buildtag.c
gcc -o drbdsetup drbdsetup.o ..../drbd/drbd_buildtag.o
bison -d -o drbdadm_parser.c drbdadm_parser.y
flex -s -odrbdadm_scanner.c drbdadm_scanner.fl
gcc -c -Wall -I..../drbd -c -o drbdadm_scanner.o
drbdadm_scanner.c
gcc -c -Wall -I..../drbd -c -o drbdadm_parser.o
drbdadm_parser.c
gcc -c -Wall -I..../drbd -c -o drbdadm_main.o
drbdadm_main.c
gcc -c -Wall -I..../drbd -c -o drbdadm_adjust.o
drbdadm_adjust.c
gcc -o drbdadm drbdadm_scanner.o drbdadm_parser.o
drbdadm_main.o drbdadm_adjust.o ..../drbd/drbd_buildtag.o
make[1]: Leaving directory
`/usr/local/src/clunix/drbd-0.7.23/user'
make[1]: Entering directory
```

	<pre>'/usr/local/src/clunix/drbd-0.7.23/scripts' make[1]: Nothing to be done for `all'. make[1]: Leaving directory `/usr/local/src/clunix/drbd-0.7.23/scripts' make[1]: Entering directory `/usr/local/src/clunix/drbd-0.7.23/documentation' To (re)make the documentation: make doc make[1]: Leaving directory `/usr/local/src/clunix/drbd-0.7.23/documentation' Build successful. [root@krkt06uldh06 drbd-0.7.23]# make V=1 make -C drbd drbd_buildtag.c make[1]: Entering directory `/usr/local/src/clunix/drbd-0.7.23/drbd' make[1]: Leaving directory `/usr/local/src/clunix/drbd-0.7.23/drbd' make[1]: Entering directory `/usr/local/src/clunix/drbd-0.7.23/user' gcc -c -Wall -I../drbd -c -o ../drbd/drbd_buildtag.o/drbd/drbd_buildtag.c gcc -o drbdsetup drbdsetup.o/drbd/drbd_buildtag.o gcc -o drbdadm drbdadm_scanner.o drbdadm_parser.o drbdadm_main.o drbdadm_adjust.o/drbd/drbd_buildtag.o make[1]: Leaving directory `/usr/local/src/clunix/drbd-0.7.23/user' make[1]: Entering directory `/usr/local/src/clunix/drbd-0.7.23/scripts' make[1]: Nothing to be done for `all'. make[1]: Leaving directory `/usr/local/src/clunix/drbd-0.7.23/scripts' make[1]: Entering directory `/usr/local/src/clunix/drbd-0.7.23/documentation' To (re)make the documentation: make doc make[1]: Leaving directory `/usr/local/src/clunix/drbd-0.7.23/documentation' make[1]: Entering directory `/usr/local/src/clunix/drbd-0.7.23/drbd'</pre>
--	--

```
Calling toplevel makefile of kernel source tree, which I
believe is in
KDIR=/lib/modules/2.6.9-42.ELsmp/build

test -f ../scripts/adjust_drbd_config_h.sh && W
KDIR=/lib/modules/2.6.9-42.ELsmp/build /bin/sh
../scripts/adjust_drbd_config_h.sh

Adjusted drbd_config.h:
--- ./linux/drbd_config.h2007-01-12 21:20:38.000000000
+0900
+++ ./linux/drbd_config.h.new2007-04-13
15:26:45.000000000 +0900
@@ -72 +72 @@
-//#define NO_MORE_DEV_FS
+#define NO_MORE_DEV_FS

make -C /lib/modules/2.6.9-42.ELsmp/build
SUBDIRS=/usr/local/src/clunix/drbd-0.7.23/drbd modules
make[2]: Entering directory
`/usr/src/kernels/2.6.9-42.EL-smp-x86_64'
mkdir -p
/usr/local/src/clunix/drbd-0.7.23/drbd/.tmp_versions
make -f scripts/Makefile.build
obj=/usr/local/src/clunix/drbd-0.7.23/drbd
gcc
-Wp,-MD,/usr/local/src/clunix/drbd-0.7.23/drbd/.drbd_size
of_sanity_check.o.d -nostdinc -iwithprefix include
-D_KERNEL__ -linclude -Wall -Wstrict-prototypes
-Wno-trigraphs -fno-strict-aliasing -fno-common -Os
-fomit-frame-pointer -g -Wdeclaration-after-statement
-mno-red-zone -mcmodel=kernel -pipe
-fno-reorder-blocks -Wno-sign-compare
-funit-at-a-time -I/usr/local/src/clunix/drbd-0.7.23/drbd
-DMODULE
-DKBUILD_BASENAME=drbd_sizeof_sanity_check
-DKBUILD_MODNAME=drbd -c -o
```

	<pre>/usr/local/src/clunix/drbd-0.7.23/drbd/.tmp_drbd_sizeof_sanity_check.o /usr/local/src/clunix/drbd-0.7.23/drbd/drbd_sizeof_sanity_check.c gcc -Wp,-MD,/usr/local/src/clunix/drbd-0.7.23/drbd/.drbd_builddtag.o.d -nostdinc -iwithprefix include -D__KERNEL__ -linclude -Wall -Wstrict-prototypes -Wno-trigraphs -fno-strict-aliasing -fno-common -Os -fomit-frame-pointer -g -Wdeclaration-after-statement -mno-red-zone -mcmodel=kernel -pipe -fno-reorder-blocks -Wno-sign-compare -funit-at-a-time -l/usr/local/src/clunix/drbd-0.7.23/drbd -DMODULE -DKBUILD_BASENAME=drbd_buildtag -DKBUILD_MODNAME=drbd -c -o /usr/local/src/clunix/drbd-0.7.23/drbd/.tmp_drbd_buildtag.o /usr/local/src/clunix/drbd-0.7.23/drbd/drbd_buildtag.c gcc -Wp,-MD,/usr/local/src/clunix/drbd-0.7.23/drbd/.drbd_bitmap.o.d -nostdinc -iwithprefix include -D__KERNEL__ -linclude -Wall -Wstrict-prototypes -Wno-trigraphs -fno-strict-aliasing -fno-common -Os -fomit-frame-pointer -g -Wdeclaration-after-statement -mno-red-zone -mcmodel=kernel -pipe -fno-reorder-blocks -Wno-sign-compare -funit-at-a-time -l/usr/local/src/clunix/drbd-0.7.23/drbd -DMODULE -DKBUILD_BASENAME=drbd_bitmap -DKBUILD_MODNAME=drbd -c -o /usr/local/src/clunix/drbd-0.7.23/drbd/.tmp_drbd_bitmap.o /usr/local/src/clunix/drbd-0.7.23/drbd/drbd_bitmap.c gcc -Wp,-MD,/usr/local/src/clunix/drbd-0.7.23/drbd/.drbd_fs.o.d -nostdinc -iwithprefix include -D__KERNEL__ -linclude -Wall -Wstrict-prototypes -Wno-trigraphs -fno-strict-aliasing -fno-common -Os -fomit-frame-pointer -g -Wdeclaration-after-statement -mno-red-zone -mcmodel=kernel -pipe -fno-reorder-blocks -Wno-sign-compare</pre>
--	--

	<pre>-funit-at-a-time -l/usr/local/src/clunix/drbd-0.7.23/drbd -DMODULE -DKBUILD_BASENAME=drbd_fs -DKBUILD_MODNAME=drbd -c -o /usr/local/src/clunix/drbd-0.7.23/drbd/.tmp_drbd_fs.o /usr/local/src/clunix/drbd-0.7.23/drbd/drbd_fs.c gcc -Wp,-MD,/usr/local/src/clunix/drbd-0.7.23/drbd/.drbd_pro c.o.d -nostdinc -iwithprefix include -D__KERNEL__ -linclude -Wall -Wstrict-prototypes -Wno-trigraphs -fno-strict-aliasing -fno-common -Os -fomit-frame-pointer -g -Wdeclaration-after-statement -mno-red-zone -mcmodel=kernel -pipe -fno-reorder-blocks -Wno-sign-compare -funit-at-a-time -l/usr/local/src/clunix/drbd-0.7.23/drbd -DMODULE -DKBUILD_BASENAME=drbd_proc -DKBUILD_MODNAME=drbd -c -o /usr/local/src/clunix/drbd-0.7.23/drbd/.tmp_drbd_proc.o /usr/local/src/clunix/drbd-0.7.23/drbd/drbd_proc.c gcc -Wp,-MD,/usr/local/src/clunix/drbd-0.7.23/drbd/.drbd_wor ker.o.d -nostdinc -iwithprefix include -D__KERNEL__ -linclude -Wall -Wstrict-prototypes -Wno-trigraphs -fno-strict-aliasing -fno-common -Os -fomit-frame-pointer -g -Wdeclaration-after-statement -mno-red-zone -mcmodel=kernel -pipe -fno-reorder-blocks -Wno-sign-compare -funit-at-a-time -l/usr/local/src/clunix/drbd-0.7.23/drbd -DMODULE -DKBUILD_BASENAME=drbd_worker -DKBUILD_MODNAME=drbd -c -o /usr/local/src/clunix/drbd-0.7.23/drbd/.tmp_drbd_worker.o /usr/local/src/clunix/drbd-0.7.23/drbd/drbd_worker.c gcc -Wp,-MD,/usr/local/src/clunix/drbd-0.7.23/drbd/.drbd_rec eiver.o.d -nostdinc -iwithprefix include -D__KERNEL__ -linclude -Wall -Wstrict-prototypes -Wno-trigraphs -fno-strict-aliasing -fno-common -Os -fomit-frame-pointer -g -Wdeclaration-after-statement -mno-red-zone -mcmodel=kernel -pipe</pre>
--	---

	<pre>-fno-reorder-blocks -Wno-sign-compare -funit-at-a-time -l/usr/local/src/clunix/drbd-0.7.23/drbd -DMODULE -DKBUILD_BASENAME=drbd_receiver -DKBUILD_MODNAME=drbd -c -o /usr/local/src/clunix/drbd-0.7.23/drbd/.tmp_drbd_receiver.o /usr/local/src/clunix/drbd-0.7.23/drbd/drbd_receiver.c /usr/local/src/clunix/drbd-0.7.23/drbd/drbd_receiver.c: In function `drbd_asender': /usr/local/src/clunix/drbd-0.7.23/drbd/drbd_receiver.c:2315 : warning: unused variable `empty' gcc -Wp,-MD,/usr/local/src/clunix/drbd-0.7.23/drbd/.drbd_req. o.d -nostdinc -iwithprefix include -D__KERNEL__ -linclude -Wall -Wstrict-prototypes -Wno-trigraphs -fno-strict-aliasing -fno-common -Os -fomit-frame-pointer -g -Wdeclaration-after-statement -mno-red-zone -mcmodel=kernel -pipe -fno-reorder-blocks -Wno-sign-compare -funit-at-a-time -l/usr/local/src/clunix/drbd-0.7.23/drbd -DMODULE -DKBUILD_BASENAME=drbd_req -DKBUILD_MODNAME=drbd -c -o /usr/local/src/clunix/drbd-0.7.23/drbd/.tmp_drbd_req.o /usr/local/src/clunix/drbd-0.7.23/drbd/drbd_req.c gcc -Wp,-MD,/usr/local/src/clunix/drbd-0.7.23/drbd/.drbd_actl og.o.d -nostdinc -iwithprefix include -D__KERNEL__ -linclude -Wall -Wstrict-prototypes -Wno-trigraphs -fno-strict-aliasing -fno-common -Os -fomit-frame-pointer -g -Wdeclaration-after-statement -mno-red-zone -mcmodel=kernel -pipe -fno-reorder-blocks -Wno-sign-compare -funit-at-a-time -l/usr/local/src/clunix/drbd-0.7.23/drbd -DMODULE -DKBUILD_BASENAME=drbd_actlog -DKBUILD_MODNAME=drbd -c -o /usr/local/src/clunix/drbd-0.7.23/drbd/.tmp_drbd_actlog.o /usr/local/src/clunix/drbd-0.7.23/drbd/drbd_actlog.c gcc -Wp,-MD,/usr/local/src/clunix/drbd-0.7.23/drbd/.lru_cache</pre>
--	---

	<pre>.o.d -fno-strict-aliasing -fno-common -Os -fomit-frame-pointer -g -Wdeclaration-after-statement -mno-red-zone -mcmodel=kernel -pipe -fno-reorder-blocks -Wno-sign-compare -funit-at-a-time -l/usr/local/src/clunix/drbd-0.7.23/drbd -DMODULE -DKBUILD_BASENAME=lrudrbd -DKBUILD_MODNAME=drbd -c -o /usr/local/src/clunix/drbd-0.7.23/drbd/.tmp_lrudrbd.o /usr/local/src/clunix/drbd-0.7.23/drbd/lrudrbd.c gcc -Wp,-MD,/usr/local/src/clunix/drbd-0.7.23/drbd/.drbd_main.o.d -fno-strict-aliasing -fno-common -Os -fomit-frame-pointer -g -Wdeclaration-after-statement -mno-red-zone -mcmodel=kernel -pipe -fno-reorder-blocks -Wno-sign-compare -funit-at-a-time -l/usr/local/src/clunix/drbd-0.7.23/drbd -DMODULE -DKBUILD_BASENAME=drbd_main -DKBUILD_MODNAME=drbd -c -o /usr/local/src/clunix/drbd-0.7.23/drbd/.tmp_drbd_main.o /usr/local/src/clunix/drbd-0.7.23/drbd/drbd_main.c ld -m elf_x86_64 -r -o /usr/local/src/clunix/drbd-0.7.23/drbd/drbd.o /usr/local/src/clunix/drbd-0.7.23/drbd/drbd_sizeof_sanity_check.o /usr/local/src/clunix/drbd-0.7.23/drbd/drbd_buildtag.o /usr/local/src/clunix/drbd-0.7.23/drbd/drbd_bitmap.o /usr/local/src/clunix/drbd-0.7.23/drbd/drbd_fs.o /usr/local/src/clunix/drbd-0.7.23/drbd/drbd_proc.o /usr/local/src/clunix/drbd-0.7.23/drbd/drbd_worker.o /usr/local/src/clunix/drbd-0.7.23/drbd/drbd_receiver.o /usr/local/src/clunix/drbd-0.7.23/drbd/drbd_req.o /usr/local/src/clunix/drbd-0.7.23/drbd/drbd_actlog.o /usr/local/src/clunix/drbd-0.7.23/drbd/lrudrbd.o /usr/local/src/clunix/drbd-0.7.23/drbd/drbd_main.o</pre>
--	---

	<pre> Building modules, stage 2. make -rR -f /usr/src/kernels/2.6.9-42.EL-smp-x86_64/scripts/Makefile.modpost scripts/mod/modpost -m -i /usr/src/kernels/2.6.9-42.EL-smp-x86_64/Module.symvers /usr/local/src/clunix/drbd-0.7.23/drbd/drbd.o gcc -Wp,-MD,/usr/local/src/clunix/drbd-0.7.23/drbd/.drbd.mod.o.d -nostdinc -iwithprefix include -D__KERNEL__ -linclude -Wall -Wstrict-prototypes -Wno-trigraphs -fno-strict-aliasing -fno-common -Os -fomit-frame-pointer -g -Wdeclaration-after-statement -mno-red-zone -mcmodel=kernel -pipe -fno-reorder-blocks -Wno-sign-compare -funit-at-a-time -DKBUILD_BASENAME=drbd -DKBUILD_MODNAME=drbd -DMODULE -c -o /usr/local/src/clunix/drbd-0.7.23/drbd/drbd.mod.o /usr/local/src/clunix/drbd-0.7.23/drbd/drbd.mod.c ld -m elf_x86_64 -r -o /usr/local/src/clunix/drbd-0.7.23/drbd/drbd.ko /usr/local/src/clunix/drbd-0.7.23/drbd/drbd.o /usr/local/src/clunix/drbd-0.7.23/drbd/drbd.mod.o make[2]: Leaving directory `/usr/src/kernels/2.6.9-42.EL-smp-x86_64' mv .drbd_kernelrelease.new .drbd_kernelrelease Memorizing module configuration ... done. make[1]: Leaving directory `/usr/local/src/clunix/drbd-0.7.23/drbd' Build successful. [root@krkt06uldh06 drbd-0.7.23]# make install make[1]: Entering directory `/usr/local/src/clunix/drbd-0.7.23/user' install -d /sbin/ install -m 755 drbdsetup /sbin/ install -m 755 drbdadm /sbin/ make[1]: Leaving directory </pre>
--	--

	<pre>'/usr/local/src/clunix/drbd-0.7.23/user' make[1]: Entering directory `/usr/local/src/clunix/drbd-0.7.23/scripts' mkdir -p /etc/ha.d/resource.d install -d /etc/rc.d/init.d/ install -m 755 drbd /etc/rc.d/init.d/drbd install -m 755 drbddisk /etc/ha.d/resource.d Don't forget to run update-rc.d or chkconfig make[1]: Leaving directory `/usr/local/src/clunix/drbd-0.7.23/scripts' make[1]: Entering directory `/usr/local/src/clunix/drbd-0.7.23/documentation' set -e; for f in drbdsetup.8 drbd.conf.5 drbd.8 drbdadm.8 drbddisk.8 ; do \ s=\${f##*.}; \ install -v -D -m 644 \$f /usr/share/man/man\${s/\$f} ; \ done `drbdsetup.8' -> `/usr/share/man/man8/drbdsetup.8' `drbd.conf.5' -> `/usr/share/man/man5/drbd.conf.5' `drbd.8' -> `/usr/share/man/man8/drbd.8' `drbdadm.8' -> `/usr/share/man/man8/drbdadm.8' `drbddisk.8' -> `/usr/share/man/man8/drbddisk.8' make[1]: Leaving directory `/usr/local/src/clunix/drbd-0.7.23/documentation' make[1]: Entering directory `/usr/local/src/clunix/drbd-0.7.23/drbd' install -d //lib/modules/2.6.9-42.ELsmp/kernel/drivers/block install -m 644 drbd.ko //lib/modules/2.6.9-42.ELsmp/kernel/drivers/block /sbin/depmod -a /sbin/depmod -e drbd.ko 2>&1 >/dev/null true make[1]: Leaving directory `/usr/local/src/clunix/drbd-0.7.23/drbd' [root@krkt06uldh06 drbd-0.7.23]# ls benchmark documentation drbd.spec.in README upgrade_0.6.x_to_0.7.0.txt</pre>
--	---

```
ChangeLog drbd      INSTALL      scripts  
upgrade_0.7.0_to_0.7.1.txt  
COPYING drbd_config.h Makefile      testing user  
[root@krkt06uldh06 drbd-0.7.23]# drepmod -a  
[root@krkt06uldh06 drbd-0.7.23]# modprobe drbd
```

5. 각종 설정파일 수정

```
[root@krkt06uldh06 etc]# vi hacommmand.cf  
"hacommmand.cf" 1L, 98Ckrkt06uldh05 61.78.57.178  
drbddisk Filesystem:::/dev/drbd0::/data::ext3 mysqld  
MysqlCheck NetCheck  
[root@n1 sbin]# cat pidchk  
#!/bin/sh  
source /usr/clx/etc/nodeinfo.cf  
  
mysqlpro=`/sbin/pidof mysqld`  
if [ -z `echo $mysqlpro` ]  
then  
#echo "process down"  
if [ -s $PIDVALUE ]  
then  
#echo "pid file up"  
rm -rf $PIDVALUE  
fi  
#else  
#echo "process up you can nomally shutdown"  
fi  
[root@n1 sbin]# vi /etc/ha.d/resource.d/MysqlCheck  
"/etc/ha.d/resource.d/MysqlCheck" 29L, 414C#!/bin/sh  
source /usr/clx/etc/nodeinfo.cf  
  
# Start, Stop, Restart Script  
  
export PATH=/usr/sbin:/sbin:/bin:/usr/bin:$PATH  
  
case "$1" in
```

```
start)/etc/ha.d/resource.d/mysql_mon localhost 5
&/usr/clx/sbin/cmitool setf node_svc $SNODE $SVCD run
down;;

stop)
#      /usr/clx/sbin/pidchkillall mysql_mon;;

*)echo "Usage: $0 {start|stop}"exit 1
esac

exit 0

~          ~

[root@n1 etc]# vi nodeinfo.cf
"nodeinfo.cf" 7L, 102CANODE=n1
SNODE=n2
SVCD=mysql
SVCTRY=
CONNECTTRY=5
PINGD=61.78.57.161
PIDVALUE=/data/$HOSTNAME.pid
~

[root@krkt06uldh06 etc]# vi ha.cf
"ha.cf" 12L, 200Clogfacility    daemon
logfile /usr/clx/log/ha-log
keepalive 2
deadtime 10
warntime 5
initdead 20
udpport 1001
baud 38400
serial /dev/ttyS0
auto_fallback off
node krkt06uldh05
node krkt06uldh06
```

```
[root@krkt06uldh06 etc]# vi erbd.cf
"erbd.cf" 69L, 1675Cskip {
As you can see, you can also comment chunks of text
with a 'skip[optional nonsense]{ skipped text }' section.
This comes in handy, if you just want to comment out
some 'resource <some name> {...}' section:
just precede it with 'skip'.

The basic format of option assignment is
<option name><linear whitespace><value>;

It should be obvious from the examples below,
but if you really care to know the details:

<option name> := valid options in the respective scope
<value>   := <num>|<string>|<choice>|...depending on
the set of allowed values for the respective option.
<num>     := [0-9]+, sometimes with an optional suffix
of K,M,G
<string>  := (<name>|W"([^\W\WW\Wn]*|\WW.)*W")+
<name>    := [/_.A-Za-z0-9-]+
}

resource drbd0 {
protocol C;
incon-degr-cmd "echo '!DRBD! pri on incon-degr' | wall
; sleep 60 ; halt -f";
startup {
wfc-timeout 120;
degr-wfc-timeout 120;
}

disk {
on-io-error detach;
}

net {
```

```
# sndbuf-size 512k;
# timeout60;    # 6 seconds (unit = 0.1 seconds)
# connect-int   10;    # 10 seconds (unit = 1 second)
# ping-int      10;    # 10 seconds (unit = 1 second)
# max-buffers    2048;
# max-epoch-size 2048;
# ko-count 4;
# on-disconnect reconnect;

}1,1Top}

syncer {
rate 100M;
group 1;
al-extents 257;
}

on krkt06uldh05 {
device    /dev/drbd0;
disk/dev/sdb1;
address   192.168.100.100:7788;
meta-disk internal;
}

on krkt06uldh06 {
device    /dev/drbd0;
disk     /dev/sdb1;
address   192.168.100.200:7788;
meta-disk internal;
}
}

~
```

6. 서비스 시작 및 종료 테스트(IP 및 프로세스, Data Failover테스트 완료)

```
[root@krkt06uldh06 ~]# /etc/rc.d/init.d/drbd start
```

	<pre>Starting DRBD resources: [d0 s0 n0]. [root@krkt06uldh06 ~]# cat /proc/drbd version: 0.7.23 (api:79/proto:74) SVN Revision: 2686 build by root@krkt06uldh06, 2007-04-13 15:26:45 0: cs:Connected st:Secondary/Secondary Id:Consistent ns:480 nr:71535396 dw:71535876 dr:3773 al:16 bm:13117 lo:0 pe:0 ua:0 ap:0 [root@krkt06uldh06 ~]# /etc/rc.d/init.d/heartbeat start Starting High-Availability services: [OK] [root@krkt06uldh06 source]# /etc/rdc.d/init.d/heartbeat satandby auto_failback: off Attempting to enter standby mode 2007/04/13_16:33:21 Going standby [all]. [OK] [root@krkt06uldh06 etc]# /etc/rc.d/init.d/cmctl start Starting CMDB: [OK] [root@krkt06uldh06 etc]# /etc/rc.d/init.d/cmctl status cmdb is running. actiond is running. lmonitord is running. clumand is running.</pre>	
--	--	--